

# Sister Light \_Table



Sister Light is a rechargeable battery-powered cordless table lamp. A "touch" control on the head allows switching on, dimming (4-step: 100%, 60%, 30%, 6%) and selecting the color temperature of the light (2700 K, 3150 K or 4000 K). It is suitable for both indoor and outdoor use and salt spray resistant (1500 h). The head of the lamp comes screwed to the stem; it can be converted to magnetic fixing and detached to become an emergency light. The base of the lamp is designed to be mechanically fixed to a table. An electronic control system monitors the remaining autonomy and ensures a constant luminous flux until the battery runs out. Recharging is therefore optimized and always properly done. The lamp comes with a USB Type-C cable for recharging; the battery charger is not included.

Ø 13,2 cm  
Ø 5,2 in



32,8 cm  
12,9 in

Ø 11 cm  
Ø 4,3 in



5 cm  
1,9 in

2 cm  
0,8 in


LED

dimmable

IP65

LD0300

|   |           |    |   |        |    |
|---|-----------|----|---|--------|----|
|  | Aluminium | A3 |  | Blue   | B3 |
|  | Gold      | O3 |  | Copper | R3 |
|  | Green     | V3 |   |        |    |



# Sister Light \_Table

## Lighting specifications

---

|                   |                      |
|-------------------|----------------------|
| source            | LED                  |
| type              | SMD                  |
| total power       | 3,0 W                |
| power LED         | 2,4 W                |
| color temperature | 2700 - 3150 - 4000 K |
| lumen lamp        | 250 - 260 - 270 lm   |
| lumen LED         | 305 - 326 - 328 lm   |
| beam angle        | 100°                 |
| CRI               | > 90                 |
| class             | E                    |
| dimmer            | TOUCH DIMMER         |
| motion sensor     | NO                   |

## Electrical specifications

---

|                   |  |
|-------------------|--|
| voltage           | 100-240V   |
| frequency         | 50/60 Hz   |
| input             | 100-240V   |
| output            | 5 Vdc max 2A   |
| batteria          | batteria a pacchetto li-lon 3 celle<br>mod.18650 2500 ma/h |
| autonomia         | 100% 8 h. - 60% 13 h. - 30% 28 h. -<br>6% 58 h.            |
| tempo di ricarica | 5 H.   |

## ACCESSORIES

---